

GTO SILICONE INTEGRAL SLEEVE WIRE

High performance silicone insulation material proven tough and versatile. Has superior resistance to fire, flame, ozone, UV and corona.

FEATURES

- GTO-10 White now packaged in smaller reels, durable for shipping **NEW!**
- Rated for 10,000 or 15,000 VAC, 150°C
- Conductor is tinned, copper 14 AWG, stranded, electrolytic tough pitch (ETP) (GTO-10 18AWG)
- Conforms to UL Standard 814 for gas tube sign and ignition cable
- Meets the integral sleeving requirement of UL Standard 814
- Classified and meets UYTA requirements of UL Standards 879, 48

SPECIFICATIONS

Part Number	Description	Unit of Measure
85373	GTO-15 Black (7.9mm / 0.311") UL/cUL Listed E226224	Box of 250'
85373-250B	GTO-10 Black (7.9mm / 0.311") UL/cUL Listed E226224	Box of 250'
85373-250W	GTO-10 White (7.9mm / 0.311") UL/cUL Listed E226224	Box of 250'
85335	GTO-10 Black (6.4mm / 0.252") UL/cUL Listed E226224	Box of 500'
85336	GTO-10 Black (6.4mm / 0.252") UL/cUL Listed E226224	Box of 1500'

Same great wire
with new
packaging and an
improved price
point!

