

# RESIN BOND ADHESIVE™

Use with our #25 Hypo Glue Applicator™ for Acrylic Plastic and Sign Trim in Channel Letters

## SPECIFICATIONS

Quart Product Number	86900
Gallon Product Number	86905
Working Time	1-2 minutes
Fixture Time	2-10 minutes
80% Strength	4 hours
Applicator #	#25
Shelf Life Unopened	Indefinite
Shelf Life Opened (with top)	2-indefinite weeks*

\*Resin bond is a single component adhesive. It will evaporate but not change it's chemical makeup or effectiveness.

Only ships via Pallet/LTL. Use #25 Hypo Glue Applicator with Resin Bond. Use on Extruded Acrylic Track. For Modified Acrylic (DR) or Polycarbonate try Channel Bond Adhesive™.

## FEATURES

- For use with acrylic plastic and sign trim (CAB) in channel letters
- Single-component (Methylene Chloride) based cement
- Thin and fast setting creating a strong bond
- Cost effective
- Clear in color
- Available in gallons and quarts
- Specifically designed to join acrylic plastic to acrylic plastic, acrylic plastic to sign trim (cellulose acetate butyrate), and changeable letter track to acrylic plastic

## BEFORE USE:

1. Read the health and safety information on the container before using.
2. Request a Safety Data Sheet and keep on file.
3. Be sure surfaces to be bonded are clean and smooth.
4. Always try a small test on scrap material before going into production.



UL File: E516868

